



The AD696/B paging microphone base can be connected to an AD615/S Tema Encoder to launch announcements on the LAN network in Multicast channels to the network amplifiers or to the IP-SIP AD600 series loudspeakers of the **SipComStage** line.

The desktop base is equipped with a "Talk" button to enable the microphone and a switch to enable the "Always on" function.

The flexible arm allows the microphone to be oriented according to the best position for the user.

The microphone, of high quality, allows to transmit crystal-clear and intelligible voice announcements.

Applications

- ◆ Vocal Announcements
- ◆ Communications
- ◆ Suitable for IP Encoder

Technical Features

Microphone capsule	: electret condenser
Polar diagram	: cardioid
Frequency response	: 50-16.000Hz
Output impedance	: 150 Ohm
Sensitivity	: -40dB (0dB 1V/Pa @1Khz)
Controls	: 1 "Talk" switch, 1 button
Signalings	: LED "Speak"
Arm	: flexible gooseneck with 2 points, removable, with XLR connector

Arm length	: 455mm
Body	: shock resistant metal alloy
Windproof cap	: black polyurethane foam
Connector/Cable	: RJ45 8-way proprietary, C5 1,5mt
Power Supply	: 5V (From AD615 Encoder)
Operating temperature	: -10°-55° C
Storage temperature	: -20°+65° C
Umidity	: 0-95% non-condensing
Dimensions	: 113x140xH35mm (without arm)
Weight	: 0,45 kg cable included

AD696/B Paging Microphone Base with AD615/S Encoder

